

GEL 436P

DESCRIPTION

GEL 436P is a finely ground attapulgite clay (hydrous magnesium aluminum silicate).

TYPICAL PHYSICAL PROPERTIES

Specific Gravity	2.35
% Moisture	18
pH (20% sol'n)	10
Color (Visual)	Gray
Wet Screen Analysis	
% retained, 400 mesh	<0.5
Bulk Density, lbs./ft. ³	
Loose	26
Packed	45

TYPICAL CHEMICAL ANALYSIS

% SiO ₂	53.4
% Al ₂ O ₃	9.6
% MgO	9.4
% CaO	2.2
% Fe ₂ O ₃	3.7
% K ₂ O	1.3
% Na ₂ O	0.4
% TiO ₂	0.4
% MnO	0.1
% Loss on Ignition (1832°F)	19.5

APPLICATION

GEL 436P is a high quality, finely ground attapulgite clay used to build viscosity and suspension properties in paints, adhesives, and other specialty applications.

GENERAL INFORMATION

GEL 436P is a finely ground, high quality attapulgite clay that is used to impart thixotropic properties to aqueous media. The material provides excellent low shear viscosity and suspension properties in water and other polar liquids. **GEL 436P** is not affected by high concentrations of dissolved electrolyte.

PACKAGING

GEL 436P is available in 50-lb. bags.

Revised 06/01/02

ZEMEX Industrial Minerals, Inc.
1040 Crown Pointe Parkway, Suite 270
Atlanta, Georgia 30338
Phone: (770) 392-8660
Fax: (770) 392-8670
Customer Service: (828) 766-2101

The information and data contained herein are believed to be accurate, but the manufacturer makes no warranty with respect thereto and disclaims responsibility for reliance thereon. This data relates only to the specific material described herein, and does not relate to use in connection with any other materials or in any process.

The manufacturer makes no warranties, express or implied, concerning this product. No warranty of fitness for any particular purpose is made, and we assume no responsibility whatever for any use of this product. This product should be used by properly trained personnel, and in compliance with applicable health and safety laws and regulations.

WARNING: This product contains free Silica (Quartz). Repeated and prolonged inhalation of dust in excess of TLV-TWA may cause delayed lung injury (Silicosis). Follow applicable OSHA, MSHA, or NIOSH standards for Crystalline Silica (Quartz). IARC has classified Crystalline Silica in Group 1, Carcinogenic to Humans, based on sufficient evidence for the carcinogenicity of Crystalline Silica in humans. The National Toxicology Program has listed crystalline silica (respirable) as a substance which may reasonably be anticipated to be a carcinogen. Airborne particles of respirable size of crystalline silica are known to the state of California to cause cancer.